

(19)



(11)

EP 1 011 464 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
23.01.2008 Bulletin 2008/04

(51) Int Cl.:
A61B 17/00 (2006.01)

(21) Application number: **98910912.9**

(86) International application number:
PCT/IB1998/000523

(22) Date of filing: **06.03.1998**

(87) International publication number:
WO 1998/038918 (11.09.1998 Gazette 1998/36)

(54) **SYSTEMS FOR PERCUTANEOUS BONE AND SPINAL STABILIZATION, FIXATION AND REPAIR**

SYSTEME ZUR PERKUTANEN KNOCHEN UND WIRBELSTABILISIRUNG, BEFESTIGUNG UND REPARATUR

SYSTEME DE STABILISATION, FIXATION ET REPARATION PERCUTANEEES, OSSEUSES ET MEDULLAIRES

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE**

- **Globermann, Oren**
46728 Herzelia (IL)
- **Magal, Elad**
46728 Herzelia (IL)

(30) Priority: **07.03.1997 US 38942 P**
07.03.1997 US 38618 P
15.01.1998 US 71531 P

(74) Representative: **Waldren, Robin Michael et al**
Marks & Clerk
90 Long Acre
London WC2E 9RA (GB)

(43) Date of publication of application:
28.06.2000 Bulletin 2000/26

(73) Proprietor: **Disc-O-Tech Medical Technologies,**
Ltd.
46724 Herzelia (IL)

(56) References cited:

EP-A- 0 493 789	EP-A- 0 748 615
WO-A-96/32899	GB-A- 2 114 005
US-A- 4 170 990	US-A- 4 313 434
US-A- 4 453 539	US-A- 4 522 200
US-A- 4 932 969	US-A- 5 102 413
US-A- 5 522 899	US-A- 5 571 189

(72) Inventors:
• **Beyar, Mordechay**
30600 Caesarea (IL)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 011 464 B1

Description

Field of the Invention

[0001] The present invention relates to systems for percutaneous bone and spinal stabilization, fixation and repair, including intramedullar bone and vertebral fixtures.

Background of the Inventions

Intramedullar Fixtures for Repair of Broken Bones

[0002] Intramedullar fixtures for use in repair of broken bones are well known in the art. Such fixtures, which generally have the form of long, narrow nails, are inserted longitudinally into the bone's intramedullar cavity, so as to connect together and jointly brace two or more sections of a severely fractured bone, and thereby promote healing.

[0003] A fixture of this type must have a radial diameter large enough to firmly and rigidly hold its position after insertion. The problem of holding the fixture in position is complicated by the fact that the intramedullar cavity of most long bones is not uniform, but is, rather, narrow at the middle of the bone and flares out at the ends. The problem is further complicated by the fact that a rod inserted into such canal does not normally provide stabilization for rotational and bending movement.

[0004] Frequently, the bone medulla must be reamed out before insertion of the fixture, to make room for the fixture therein. Such reaming destroys tissue within the bone and may consequently retard proper healing. Therefore, various intramedullar nails and fixtures have been designed to have a narrow shape during insertion and then to expand radially outward to fit the shape of the intramedullar cavity and hold firmly therein.

[0005] For example, U.S. Patent No. 4,204,531 to Aginsky, describes an intramedullar nail with an expanding mechanism. The nail includes an outer tubular sheath, a rod-shaped element longitudinally movable in the sheath, and an expandable element having two or more spreadable longitudinal branches at the front (inner) end of the nail. The nail is inserted into the medullar cavity of a bone, front end first, leaving the rear end of the nail to protrude out of the end of the bone. The rod-shaped element is then pulled back, causing the branches of the expander element to spread radially outward, thereby anchoring the front end of the nail within the intramedullar cavity.

[0006] Similarly, U.S. Patent No. 4,854,312 to Raftopoulos et al., describes an expanding intramedullar nail. The nail is formed of two elongate members. A first one of the members has an articulated channel, which slidably engages the second member. After the nail is inserted into the intramedullar cavity, the second member is slid longitudinally relative to the first, causing the end of the second member to bend, so that the nail

spreads laterally within the cavity and is anchored in place.

[0007] U.S. Patent No. 4,313,434 to Segal, describes a method for fixation of fracture of long bones using a flexible, inflatable bladder inside the intramedullar cavity. A small opening is drilled in the bone, and the bladder is inserted through the hole into the intramedullar cavity. The bladder is then inflated with sterile air and sealed, to fixate the bone. After the fracture has healed, the bladder is deflated and removed.

[0008] U.S. Patent Nos. 5,423,850 and 5,480,400 both to Berger, describe methods and devices of bone fixation using a balloon catheter. The catheter, with the deflated balloon at its distal end, is inserted into the intramedullar cavity, past the fracture site. In the '850 Patent, the balloon is inserted by guiding it along guide wires that are fed through the cavity, before introducing the catheter. Once fully inserted in the cavity, the balloon is inflated to anchor it in place, and the catheter is tightened against the balloon to provide compression to the fracture.

[0009] The intramedullar fixtures and methods of implantation thereof that are described in all of the above-mentioned patents require that a portion of the expandable intramedullar fixture be left protruding through the patient's skin. Such protruding portions, however, increase the likelihood of postoperative infection and interfere with mobilization of the bone. Accordingly, it is an object of the present invention to provide methods and devices which eliminate the need for such protrusions.

[0010] In addition to fracture of large bones, fracture of long small bones is also a very common occurrence. However, a simple treatment which allows early mobilization with fracture stabilization is not currently available.

[0011] Varela and Carr in an article entitled "Closed Intramedullary Pinning of Metacarpal and Phalanx Fractures," in *Orthopedics* 13 (2), 213-215 (1990), describe one method for fixation of finger fractures using K-wires. To fixate a fractured finger bone, several such wires, slightly bent, are inserted one after another into the intramedullar cavity. Each wire is inserted through a respective hole drilled near one end of the bone. Typically, between two and five wires are needed to fixate the bone. After insertion, the wires are cut off flush with the bone surface, and the skin is closed over the insertion site.

[0012] However, the treatment of choice today for fractured small tubular bones is the insertion of a thin metal rod (intramedullary nailing). To prevent this rod from moving, an edge of the rod is left projecting from outside the bone, such as is done in metatarsal bone fracture nailing where the end of the rod projects out of the finger tip. This fixation, however, prevents the patient from using the finger or the broken bone limb. It also does not allow good rotational stabilization. In addition, it can also result in infection due to communication between the bone medulla and the exterior of the body.

[0013] Some patents and methods for the fixation of small bones without use of protruding rods currently exist in the art. Examples include, for example, Lewis, R.C.,

Jr., Nordyke, M., Duncan, K., Clinical Orthopedics Related Research, 1987, 214 (85-92); Nordyke, M.D., Lewis, R.C., Janssen, H.F., Duncan, K.H. J. of Hand Surgery, 1988, 13/11 (128-134); Varela, C.D., Carr, J.B., Orthopedics, 1990, 13/2: 213-215; and, WO 94/12112, US 4204531, and US 4854312.

[0014] One method in particular is described in an article "Expandable Intramedullary Device for the Treatment of Fractures in the Hand", Royce C. Lewis et al., Clinical Orthopedics and Related Research, Tech. Ortho., 1989, 1:18-91. In this article, an expandable intramedullary nail is inserted after the fractured bone is opened and the nail is inserted through the broken part. The nail is inserted through the fracture and not through the bone extremities. Yet, there still exists a need for a percutaneous minimal trauma insertion of an internal fixator for small bones which does not necessitate exposure of the bone surface.

[0015] Intramedullary nailing through the finger tip is also discussed in the article "Closed intramedullary pinning of metacarpal fractures", Varela, C.D.; Carr, J.B., Orthopedics, 1990, 13/2: 213-215. However, this nailing does not involve an expandable nail.

[0016] Numerous of the bone fixation patents mentioned above involve implantation of different metal devices (i.e., Nitinol, Titanium, etc.). Another possibility is to use a detachable inflatable balloon as an expandable intramedullary bone fixator. There are patents that exist today for bone fixation with a balloon, but these do not provide intramedullary nailing. They provide only a joining effect as in the pulling of one broken bone towards the other. Examples of these include U.S. Patent Nos. 5,423,850 and 5,480,400 (described above).

[0017] Accordingly, a variety of significant shortcomings exist in the present art of fracture stabilization. To address these problems, the present inventors have provided an intramedullary nailing which is accomplished for example, by using a detachable intramedullary balloon located at the middle of the fracture, and extended across both bone segments, a improved device is provided which addresses the numerous shortcomings of the prior art. Such devices provide the patient with a rapid post-surgery fracture stabilization resulting in mobilization of the limb and reduced chance for infection, as well as the possibility of removal after bone healing, if needed.

Intravertebral Disc Ablation and Spacer Placement

[0018] Back pain is a widespread ailment which is often attributed to disc pathologies and vertebral instability. Nowadays, the treatment of choice of spinal fusion involves disc removal followed by implantation of a plate with or without screws into the intervertebral space (See e.g., U.S. Patent No. 5520690, U.S. Patent No. 5522816, and U.S. Patent No. 5529899). The procedure also involves implantation of a bone graft in the intervertebral space.

[0019] Patents and applications employing artificial in-

tervertebral discs currently exist, although they have not yet been proven successful in patients (U.S. Pat. No. 4,759,769; WO 92/14423; WO 90/00037; WO 96/37170). Existing treatments involve introductory surgery for removal of the original spinal disc tissue and placement of the intervertebral support. An intervertebral spacer and stabilizer is placed within the intervertebral space followed by the removal of the damaged disc and cleaning of the intervertebral bone surfaces by use of different cutters and retractors (U.S. Pat. No. 4,904,260 and U.S. Pat. No. 5,645,598 for example). A bone graft is then implanted to facilitate spine fusion.

[0020] All procedures utilizing the above method require actual opening and dissection of the back and/or the abdomen or performing the procedure laparoscopically. Accordingly, there is currently a need in the art for a percutaneous non-laparoscopic type minimally invasive technique to facilitate and improve the current method for spine fusion.

[0021] In addition, the disc ablation procedure may involve the interposition of a spacer in the intervertebral space to support the vertebrae until spine fusion is achieved by osteogenesis. The existing spacers are constructed with a fixed diameter according to the space needed to be kept in the intervertebral area. Although one spacer has been disclosed which expands by rotating a screw, it only expands upwards and downwards, and therefore still has a large insertion profile. This does not allow for the insertion of the device percutaneously in a minimally invasive technique. As discussed in greater detail below, there is a need for a spacer or prosthesis that is created with a small diameter and which can expand radially once implanted. In addition, as also discussed below, there is also a need for an intervertebral tissue extractor which can likewise function percutaneously for use in the procedures described.

Intervertebral Disc Prostheses

[0022] Intervertebral disc prostheses are also known in the art. Such a prosthesis is generally inserted into the intervertebral space following the removal of all or a part of the disc matter from the space. Upon insertion, the prosthesis holds two adjacent vertebrae apart from each other, so as to maintain the vertebrae in an anatomically correct spacing and orientation. Following surgery to implant the prosthesis, bone generally grows from the vertebrae into and around the prosthesis, thereby holding the prosthesis firmly in place and preventing undesirable motion of the vertebrae relative to each another.

[0023] U.S. Patent Nos. 4,772,287 and 4,904,260 to Ray et al., describe prosthetic disc capsules having a generally cylindrical shape and containing a gel material having properties similar to those of the disc matter. After removal of a portion of the disc matter, two such prosthetic capsules are implanted in the disc space, one on either side of the sagittal axis of the spine. The capsules may be implanted in a deflated state and then inflated

with the gel to a pressure sufficient to hold the adjoining vertebrae apart.

[0024] To implant the prosthetic disc capsules in the disc space, it is necessary to open the patient's back and perform a partial laminectomy to gain access to the disc space. Such open laminectomy is a major surgical procedure, with attendant risks, side effects and long recovery time. Other disc prostheses, as described, for example, in U.S. Patent Nos. 3,875,595, 4,349,921, 3,867,728, 4,554,914, 4,309,777, 3,426,364, and 4,636,217, similarly require major surgery for implantation thereof.

[0025] In response to the risks and lengthy recovery period associated with open surgery for treatment of bulging or herniated discs, an alternative, minimally-invasive surgical technique of percutaneous discectomy has been developed. In percutaneous discectomy, a narrow cannula is inserted into the disc space in a lateral approach through a small incision in the patient's side. The lateral approach to the disc obviates the need to cut through bone and/or substantial amounts of muscle, as required by other surgical methods known in the art. Surgical tools are passed through the cannula to cut away and remove disc material, so as to relieve the outward pressure of the disc on surrounding nerves and thus to alleviate the pain caused by the bulging or herniated disc.

[0026] Percutaneous discectomy can be performed as an outpatient procedure and, when successful, allows the patient to return to full activity after only a short recovery period. The procedure is successful only in about 70% of cases or less, however, and does not allow the full range of treatment afforded by open back surgery. For example, disc prostheses and methods of implantation of such prostheses that are known in the art are not suitable for use in the percutaneous approach.

[0027] The vertebrate spine is the axis of the skeleton, on which the body parts hang. The bony vertebral bodies of the spine are separated by intravertebral discs, which serve as a cushion between vertebral segments of the axial skeleton. These discs comprise a fibrous annulus and a nucleus, which is a gel-like substance, contained within the annulus. A disc herniation occurs when the tissue of the nucleus bulges out of the annulus. The herniated nucleus may exert pressure on a spinal nerve adjacent to the disc, resulting in pain or loss of muscle control. The normal procedure in such cases is to remove the herniated disc tissue in open surgery, but this is a major procedure with long recovery and potentially serious side effects.

[0028] In response to the dangers and complications of open spinal surgery, minimally invasive procedures for removal of herniated tissue have been developed. One type of such procedure as described above, is percutaneous discectomy, in which herniated tissue of the nucleus of the disc is removed from the patient's body. Apparatus for such procedures is described, for example, in U.S. Patent No. 5,131,382. The nuclear tissue is removed through a cannula, which is inserted through a

small incision, preferably in the patient's side, into the intervertebral space. By making the incision as small as possible and entering the body laterally, rather than dorsally, trauma to the patient is minimized. Removal of the herniated tissue is a long process, however, frequently requiring removal and reinsertion of resection tools many times.

[0029] In some discectomy procedures, after the tissue is removed, a disc prosthesis is inserted to replace the nucleus and possibly the annulus, as described above, and in PCT publication WO 96/11643 for example. Generally, it is desired that the two adjacent vertebrae fuse together, around the prosthesis. In order to facilitate insertion of the prosthesis and encourage subsequent bone fusion, the disc tissue should be thoroughly cleaned out during discectomy. However, percutaneous discectomy procedures and devices known in the art do not generally achieve such thorough cleaning.

[0030] WO 96/32899 describes a device for intramedullary fixing having a nail with at least one expanding chamber.

[0031] EP 0 493 789 describes a device having a tube of non elastic material for inserting into the narrow cavity of bone according to the preamble of claim 1.

Summary of the Invention

[0032] It is an object of the present invention to provide improved devices and methods for intramedullary fixation of fractured bones.

[0033] It is an object of the invention to provide devices and methods for fixation of the humerus and other long bones.

[0034] It is an object of the invention to provide devices and methods for fixation of fractures of the phalanx bones or other small bones of the hands and feet.

[0035] It is an object of the present invention to provide devices and methods which allow intramedullary bone fixation using minimally-invasive surgical procedures, so as to generally reduce operative trauma and allow speedier post-operative recovery.

[0036] It is an object of the present invention to provide devices and methods for percutaneous bone and spinal stabilization, fixation and repair.

[0037] It is a further object of the present invention to provide a percutaneously inserted intramedullary bone fixation device for the stabilization of fractured bones.

[0038] It is an object of some aspects of the present invention to provide devices for intramedullary fixation that allow mobilization of a bone within a short time of fixation thereof.

[0039] It is an object of other aspects of the present invention to reduce the risk of post-operative infection following intramedullary fixation.

[0040] It is a further object of the present invention to provide inflatable balloon fixation devices for intramedullary nailing.

[0041] It is a further object of the present invention to

provide fixation devices having a valve for inflation and deflation of the devices.

[0042] It is a further object to provide intramedullary devices having fixation elements for anchoring the devices against the inner surface of a bone.

[0043] It is a further object of the present invention to provide devices which provide for a less invasive surgical treatment of intervertebral spine fusion.

[0044] It is a further object of the present invention to provide a minimally invasive device for treatment of intervertebral spine fusion which includes the extraction of intervertebral tissue and the placement of an intervertebral spacer.

[0045] It is an object of the present invention to provide an improved disc prosthesis for implantation in the intervertebral disc space.

[0046] It is a further object of some aspects of the present invention to provide a disc prosthesis suitable for implantation using minimally invasive methods of percutaneous discectomy. It is another object of these aspects of the invention to provide devices for use in percutaneous implantation of the prosthesis.

[0047] It is a further object of the present invention to provide a prosthesis whose size can be increased long after implantation, without the need for a second surgical procedure.

[0048] Further objects of the invention will become apparent upon reference to the drawings, description and/or claims herein.

[0049] In a first aspect, the present invention provides a medical device for treatment of broken bones having an intramedullary cavity, the bone being provided with a bore formed through the exterior surface of the bone and extending into the intramedullary cavity, comprising :

a bone fixture according to claim 1 for insertion through the bore of the bone and into the intramedullary cavity, said bone fixture comprising an inflatable, diameter-expandable, non-memory metallic tube having an exterior circumferential surface, said tube having a reduced first diameter for insertion through the bore and into the intramedullary cavity and a second expanded diameter, wherein said bone fixture will radially increase in diameter from said reduced first diameter to said expanded second diameter by inflation when fluid is supplied to the interior of said device, and when said bone fixture radially increases in diameter from said reduced first diameter to said second expanded diameter, at least a portion of said exterior circumferential surface coming into contact with a portion of the side wall of said intramedullary cavity upon said bone fixture increasing to said second expanded diameter.

[0050] Preferably, the reduced diameter is sufficiently small such that said fixture can be inserted into the bone through a hole which is smaller in diameter than the medulla of the bone. More preferably, the reduced diameter

is sufficiently small such that said fixture can be inserted into the bone through a syringe.

[0051] Preferably, the expanded diameter is sufficiently large such that said expanded diameter extends across substantially the entire width of the intramedullary cavity of the bone.

[0052] The fixture may further comprise a valve or longitudinal bars. More preferably the fixture comprises a curved surface before expansion, said surface being curved to form a series of connected bulbous sections. The fixture may have a circumferential wall comprising four bulbous sections separated by thin wall sections,

[0053] The fixture may comprise at least two of said longitudinal bars.

[0054] The fixture may comprise at least one hairpin loop between said two longitudinal bars, more preferably four longitudinal bars and four hairpin loops.

[0055] Preferably said fixture is sized for treatment of a broken bone of the hand, foot, leg or arm.

[0056] The fixture may be substantially tubular in shape after expansion.

[0057] The fixture may expand to adjust to and rest against the inner surface and shape of the bone cavity upon said expansion.

[0058] Preferably, the fixture increases in diameter by at least 40% when said fixture increases from said reduced diameter to said expanded diameter. The fixture preferably comprises at least one sheet of said self-expanding material, more preferably at least two sheets.

[0059] The fixture preferably comprises a generally cylindrically rolled spiral structure in said reduced diameter, more preferably said spiral structure at least partially unrolls as said fixture expands from said reduced diameter to said expanded diameter.

[0060] The fixture may be cylindrical in said expanded diameter and comprises a plurality of longitudinal ribs and substantially arcuate circumferential struts, said ribs being interconnected by said struts. More preferably, the fixture comprises a central axis, said struts being bent inward about a midpoint toward said central axis when said fixture is in said reduced, diameter. The fixture may also comprise a circumferential wall, said fixture comprising a plurality of openings in said circumferential wall.

[0061] In a further, independent aspect, the present invention provides a medical treatment system for treatment of bones, comprising:

a bone fixture for insertion through the bore of the bone and into the intramedullary cavity, said bone fixture comprising an inflatable, diameter-expandable, non-memory metallic tube having an exterior circumferential surface, said tube having a reduced first diameter for insertion through the bore and into the intramedullary cavity and a second expanded diameter, wherein said bone fixture will radially increase in diameter from said reduced first diameter to said expanded second diameter by inflation when fluid is supplied to the interior of said device, and when said

bone fixture radially increases in diameter from said reduced first diameter to said second expanded diameter, at least a portion of said exterior circumferential surface coming into contact with a portion of the side wall of said intramedullary cavity upon said bone fixture increasing to said second expanded diameter.

a cannula for insertion of said bone fixture into a bone, said cannula comprising a lumen, said bone fixture being of a sufficiently small size in said reduced diameter that said bone fixture can be inserted into said bone by use of said cannula.

[0062] Figure 19 summarises the classes of methods and devices for bone fixation and spacing which are described herein, devices for bone fixation, spacing and prostheses may also be referred to, for brevity, as bone therapy devices. Likewise, the term prosthesis, implant, and fixture are used interchangeably herein.

[0063] As described below, these devices and their associated methods can be divided into 3 general categories or groups: (I) Self Expandable Implants; (II) Implants Expandable by External Power; and (III) Solid Phase Formation Devices. Devices can be constructed according to the embodiments of each of these groups, and can be employed for either intramedullary or intervertebral applications.

Classes of Bone Fixation Devices and Methods

[0064]

Group I: Self Expandable Implants. Self expandable implants and related methods utilize the energy stored within the implant material itself, such that when a holding mechanism or restraining force is released from the implant, the implant material reverts to its original shape and/or diameter. The material may be restrained in a small diameter, for use during implantation, and reverts to a larger diameter after implantation, for fixation of the bone. The holding mechanism utilized can be incorporated into the device or around it,

Group II: Implants Expandable by External Power. Implants which are expandable by external power utilize energy which does not exist in the device but originates from an outside source, to change the shape of the implant. Numerous different forms of external power can be utilized in accordance with the present invention. At least four alternative types of external power are contemplated:

(1) Heat. Various materials and/or configurations of material can be used in which the application of external heat to the implant (whether from a mechanical source, or body heat itself) causes a change in shape of the implant.

(2) Balloon Expandable Devices. In a second series of external power embodiments, an expandable balloon is used to change the shape of an implant. In these embodiments, the inflation of a balloon causes plastic deformation of the implant material, resulting in deformation of the device.

(3) Balloon Devices. In a third series of external power embodiments, the implant device is itself a balloon. This balloon device is inflated using hydraulic pressure by the insertion of fluid into the balloon's interior, thereby enlarging the device's diameter. In these embodiments, the pressure of the fluid within the sealed balloon provides the energy to support the balloon in its expanded shape.

(4) External Force Devices. In a fourth series of external power examples, a mechanism is utilized for application of force to the implant. In these examples, the system is designed such that force is transferred inwards, which acts eccentrically from the implant lumen causing an increase of the implant diameter.

Group III. Solid Phase Formation Devices. In these devices, a material which solidifies (e.g. by polymerization) is inserted into a balloon, forming a solid which has a new shape. This material can have two-componential cement properties, and can be formed of epoxy or polymer. The material is compressed into the balloon and solidifies by change in temperature or humidity.

[0065] As disclosed herein, each of these types of devices and methods can be used for intramedullary or intervertebral treatments. Moreover, while different embodiments of the present inventions are discussed in separate sections below, it will be apparent that the disclosures of each section are meant to supplement each other and interrelate. Accordingly, the disclosures of each of the examples provided herein may be further relevant to and supplement the disclosures of other examples.

[0066] A variety of different bone therapy devices and methods are disclosed in further detail below.

Intramedullary Fixtures

[0067] In the intramedullary fixture embodiments of the present invention, a radially-expandable intramedullary fixture is inserted percutaneously into a fractured bone. The fixture is inserted through a hole in the bone which is smaller in diameter than the medullar canal. In the preferred embodiments, the fixture is preferably inserted, using a syringe, through the end of a fractured bone and into the medulla. During insertion, the fixture is maintained in a closed configuration, i.e. a first, reduced di-

ameter. The fixture is inserted so that it extends across the site of the fracture in the bone. When the fixture is properly placed within the bone, the syringe is withdrawn. It is highly preferred that the fixture be placed entirely within the bone, with no outward protrusion.

[0068] Once in place, the fixture expands radially outward, assuming an open configuration, i.e., a second, expanded diameter, and anchoring itself in place. Upon expansion, the radially expandable device extends through the bone, across both sides of the fracture, thus functioning as an intramedullary bone fixator. The expanded fixture thus holds the pieces of the broken bone together and provides reinforcement against both axial and lateral forces on the bone. Fixtures as those disclosed herein can be provided and sized for long bones, such as the femur, tibia, fibula, humerus, ulna and radius or for smaller bones, such as a phalanx.

[0069] After the fixture has been inserted, the skin wound made by the syringe is closed and allowed to heal over the bone. With the employment of the minimally invasive percutaneous procedure, which excludes all post-implantation communication with a contaminated skin surface, the present invention fixates the fractured bone rapidly, and allows mobilization of the patient's limb in minimal time and with a lower infection risk. Thus, when the fixture is used to repair a broken bone in an extremity (for example, a phalanx fracture in a finger), the patient can begin to move the extremity very shortly after the insertion. Such rapid mobilization promotes healing and reduces muscle atrophy. The patient regains use of the broken bone as quickly as possible. Even more importantly, healing proceeds without the need for extensive physiotherapy, which is typically required after the prolonged periods of immobilization commonly encountered when intramedullary nails known in the prior art are used. Furthermore, since there is no fixture left protruding through the skin after the insertion, post-surgical infection and other complications are reduced.

[0070] In the preferred embodiments, the implant is made of bio-compatible metals like titanium, S.S. 316 or suitable polymers. Preferably, after insertion, the radial expansion of the fixture is such that its diameter substantially increases. Thus, the diameter can increase by at least 20%, by 40%, by 50%, or more if desired. This large factor of Expansion is advantageous in that during insertion, the unexpanded fixture is narrow enough to fit easily into the bone medulla. In contrast, the fixture expands after placement such that its diameter fills substantially all of the intramedullary cavity (i.e., such that the fixture extends across substantially all of the width of the bone) so that the bone is firmly fixated.

[0071] Thus, more generally, the initial size of the fixture maintains a reduced diameter small enough to be passed through a needle so as to be inserted into a bone through a syringe, and is capable of expanding to an expanded diameter large enough to fill substantially all of the intramedullary cavity of the bone in question, for fixation of the bone. The fixture is preferably substantially

rod like (i.e. tubular in shape) after expansion.

[0072] Fixtures in accordance with preferred embodiments of the present invention generally fixate the bone more firmly than K-wires used for this purpose, as described in the above-mentioned article by Varela and Carr. The fixtures of the present invention require formation of only a single hole in the bone for intramedullary insertion, rather than multiple holes as is the case with K-wires.

[0073] In embodiments of the present invention involving the application of external energy, a balloon may be inserted inside the fixture and inflated to expand the fixture. After the fixture is expanded, the balloon is preferably deflated and withdrawn although it can also be left implanted.

[0074] In another embodiment of the invention, the intramedullary bone fixator is made of an inflatable balloon.

[0075] In other embodiments of the present invention, the fixture itself comprises a balloon, which is inserted into the intramedullary cavity.

[0076] This balloon fixture is also preferably inserted using a syringe. After the placement of the syringe in the intramedullary space, a sleeve can be inserted therein, through which the balloon is inserted. Once the balloon is positioned and the sleeve and syringe are taken out, the balloon is inflated and detached of the inflating device which is also taken out. The same procedure can also be performed without a sleeve, with or without a guide wire.

[0077] Once the balloon is in place, it is inflated to fixate the bone. This can be accomplished with a biocompatible solidifying fluid under pressure from an external source, causing the balloon to expand radially outward to fixate the bone. The balloon is then sealed, and the external fluid source is disconnected.

[0078] Preferably, the solidifying fluid comprises a monomer material that polymerizes within the balloon, or alternatively, a two-component cement, such as an epoxy. Such solidifying fluid materials are known in the art. The fluid's solidification is preferably catalyzed by the increased temperature and/or humidity within the bone medulla.

[0079] Alternatively, when a non-solidifying non-compressible fluid is used, the need should arise, the balloon can be perforated and removed utilizing the same basic technique (albeit in reverse) with which it was inserted.

[0080] In some of the preferred embodiments, the balloon can also include an internal structure, for example, resilient longitudinal wires. These wires can be fabricated from metal, and can extend lengthwise down the inner side of the balloon. While the balloon is deflated, the structure holds the balloon in a narrow, elongated, substantially closed configuration, so as to ease the insertion of the balloon into the bone. After the balloon has been inserted and inflated, the structure provides additional mechanical strength to the fixture, especially against shear forces. This gives the balloon the elasticity as well as the strength of a bone fixator, once the balloon is in-

flated in the intramedullary space.

[0081] Preferably, after the balloon is inserted into the bone, the balloon is filled with non-compressible fluid. In the preferred embodiments, the balloon has a valve to prevent fluid from escaping (while also allowing fluid to be released, once desired). Upon filling the balloon with fluid, it expands so that it substantially fills the intramedullary cavity. Preferably, an X-ray image is taken of the bone with the balloon inside (preferably while the balloon is still in a partially or non-expanded state). The balloon's internal structure is then observed in the image to ascertain that the balloon is properly positioned, before fully inflating the balloon with the solidifying fluid. In particular, the longitudinal wires will show up on the X-ray image so that proper positioning can be verified.

[0082] In the preferred embodiments of the invention, a metal balloon is utilized which has a unidirectional valve, and which is inflated with a high pressure fluid (preferably saline). The balloon is constructed having longitudinal bars which act as fixational elements, so that when inflated, the fixational elements or bars are compressed against the inner surface of the bone cortex, preventing rotational movement between the broken parts of the bone and preventing bending. This embodiment presents an advantage over standard intramedullary nails as no interlocking is needed due to the fact that the longitudinal rods prevent rotation. The nail may also have a medial longitudinal canal to facilitate performing the insertion procedure over a guide wire. During removal, the retrieval device is mounted on the tip of the implanted nail to open the valve, releasing the high pressure within: the nail and allowing device diameter decrease.

[0083] Fixtures and methods of bone fixation in accordance with the embodiments of the present invention described herein are advantageous for fixation of fractured long bones or short bones. For example, the fixtures of the present invention may be used for fixation of the bones of the arms, legs, hands or feet. Thus, they may be used for fixation of the, phalanges of the fingers or toes, the femur, the humerus, the metacarpals, the metatarsals, the tibia, the fibula, or so forth. It will be appreciated that fixtures in accordance with the present invention can be easily adapted to the necessary size for the broken bone required, by one of ordinary skill in the art.

Brief Description of the Drawings

[0084]

Figure 1 is a schematic, isometric view of a self-expanding intramedullary fixture, in accordance with an example useful for understanding the present invention.

Figure 2A is a schematic, sectional illustration showing a self-expanding intramedullary fixture in a first, closed configuration, in accordance with an example useful for understanding the present invention.

Figure 2B is a schematic, sectional illustration showing the fixture of Figure 2A in a second, open configuration, in accordance with an example useful for understanding the present invention.

Figures 3A-3C are schematic, sectional illustrations showing the use of the fixture of Figure 1 in fixation of a fractured bone, in accordance with a preferred embodiment of the present invention.

Figure 4A is a schematic, isometric representation of another self expanding intramedullary fixture, in an open configuration, in accordance with an example useful for understanding the present invention.

Figure 4B is a schematic, sectional illustration showing the fixture of Figure 4A in a closed configuration, wherein a holding pin is inserted along a central axis of the fixture, in accordance with an example useful for understanding the present invention.

Figure 5A is a schematic, end view of still another self-expanding intramedullary fixture in an open configuration, in accordance with an example useful for understanding the present invention.

Figure 5B is a schematic illustration showing preparation of material for fabrication of the fixture shown in Figure 5A, in accordance with an example useful for understanding the present invention.

Figure 5C is a schematic, sectional view of the fixture of Figure 5A, in a closed configuration with an internal holding pin, in accordance with an example useful for understanding the present invention.

Figure 6 is a schematic representation of an intramedullary balloon fixture, in a non-inflated state, in accordance with a preferred embodiment of the present invention.

Figures 7A-7D are schematic, sectional illustrations showing the use of the fixture of Figure 6 in fixation of a fractured bone. The figures illustrate the steps of insertion of the fixture, inflation of the balloon and removal of the inflation mechanism.

Figures 8A and 8B are side and sectional views, respectively, of an inflatable intramedullary fixture, in a deflated configuration, in accordance with a preferred embodiment of the present invention.

Figures 9A and 9B are sectional and isometric views, respectively, of an inflatable intramedullary fixture, in an inflated configuration, in accordance with a preferred embodiment of the present invention.

Figures 10 (a) - (d) are perspective views showing two devices for bone fixation in open and closed positions. These devices can be opened by a transfer of heat (e.g. if they are constructed from shape memory material) or can be opened by use of a balloon, in accordance with an embodiment of the present invention. Figures 10(a) and (b) are illustrations of a first of the device, shown in compressed and expanded configurations example respectively. Figures 10 (c) and (d) are illustrations of a second example of the device, shown in compressed and expanded configurations respectively.

Figure 11 is a schematic cross sectional illustration of a bone fixation device whose height can be mechanically varied, in accordance with an example useful for understanding the present invention. It is shown in closed (Figure 11a) and open (Figure 11b) configurations. The device can include hinges at its joints or joints that undergo plastic deformation.

Figure 12 is a schematic isometric view of an expandable intervertebral spacer and intramedullary bone fixator, in accordance with a preferred embodiment of the present invention. The design is shown in the figure without a locking finger and with multiple surface openings.

Figure 13A is a schematic cross sectional view of an intervertebral bone spacer and intramedullary bone fixator, in accordance with a preferred embodiment of the present invention.

Figure 13B is a schematic cross sectional view of the device of Figure 13A, shown in its compact, reduced diameter state for insertion.

Figure 13C is a sectional view of a modified version of the device of Figures 13A-B, shown in its expanded state, with multiple locking mechanisms.

Figure 14A is a schematic, top view of an intervertebral disc prosthesis.

Figure 14B is a schematic, cross-sectional view of the prosthesis shown in Figure 14A.

Figure 15 is a schematic, isometric illustration showing the insertion of the prosthesis of Figures 14A and 14B into the intervertebral disc space of a patient.

Figure 16 is a schematic, sectional view in a coronal plane, showing the placement of the prosthesis of Figures 14A and 14B in the disc space.

Figure 17A is a schematic, sectional view in the coronal plane of Figure 16, showing the inflation of the prosthesis of Figures 14A and 14B, within the disc space.

Figure 17B is a schematic, sectional view in an axial plane through the disc space, illustrating the inflated prosthesis as shown in Figure 17A; and

Figures 18A, 18B and 18C are respectively a sectional view, a top view and an isometric view of a disc prosthesis (with a portion of an inflator mechanism).

Figure 19 is a chart summarizing the various methods and devices for bone fixation and intervertebral spacing.

Figure 20 depicts views of additional preferred embodiments of an intramedullary fixation device. Figure 20A is a perspective view of this intramedullary fixture. Figure 20B is a cross sectional view of the intramedullary fixture of Figure 20A. Figure 20C is a schematic, partial side view of the intramedullary fixture of Figures 20A and 20B.

Figure 21 depicts views of additional preferred embodiments of an intramedullary fixation device having a valve. Figure 21A illustrates a longitudinal cross section of the device. Figure 21B illustrates a cross

sectional view of the device of Figure 21A, the device being shown in the compressed configuration, with the view being taken in cross section along line A-A of Figure 21A. Figure 21C illustrates a cross-section of the expanded configuration of the device of Figure 21B, also taken along line A-A of Figure 21A.

Figure 21D is an additional embodiment of the device shown in Figures 21A-C. The device is further provided with a fixed diameter segment which is located in the area of a fracture.

Figure 22A presents two cross sectional views of another embodiment of the intramedullary nail invention. Cross sectional views of both the constricted and expanded configurations or states are shown in the figure, with these constricted and expanded configurations being superimposed for comparison purposes.

Figure 22B presents two cross sectional views of another embodiment of the intramedullary nail invention. As in Figure 22A, cross sectional views of both the constricted and expanded configurations or states are shown superimposed for comparison purposes.

Figure 23 illustrates the medial longitudinal canal which can be provided as an additional embodiment of the invention. The canal is provided for location of the fixture on a guide wire to facilitate positioning. Figure 23A is a perspective view of the fixture, having the canal therein, and Figure 23B is a schematic of the fixture, showing the canal extending there-through.

Detailed Description of the Invention and the Preferred Embodiments

[0085] Features of the invention are further illustrated by reference to the figures, the following description and the claims, which provide additional disclosure of the invention in various preferred embodiments.

[0086] Figure 1 is a schematic, isometric representation of a self-expanding intramedullary fixture 20, in accordance with an example useful for understanding the present invention. Fixture 20 is preferably constructed of two sheets 22 and 24 of resilient, biocompatible material, preferably a superelastic material or a shape memory material, as is known in the art. Nitinol is preferred. Alternatively, the fixture may be constructed from another biocompatible metal, such as titanium, or a plastic or polymer material.

[0087] Sheets 22 and 24 are initially rolled tightly together into a cylindrical form. Each sheet of this compacted form is tightly rolled (as generally shown in Figure 2A), and fixture 20 is inserted, in this compacted form, into the intramedullary cavity of a bone (Figure 3B), as described below. When the fixture is then released inside the bone, the resilience of sheets 22 and 24 causes them to partially unroll into an expanded state (as generally shown in Figure 2B), so that fixture 20 expands radially

outward to assume an increased diameter, as shown in Figure 1.

[0088] Preferably, outer edges 26 and 28 of sheets 22 and 24, respectively, are formed so that when fixture 20 is released inside the bone, the edges bend radially outward, as shown in Figure 1. Edges 26 and 28 will then engage an inner surface of the bone surrounding the intramedullary cavity, so as to hold fixture 20 firmly in place and prevent sliding or rotation of the bone relative to the fixture. Preferably, edge 26 is bent at an acute angle, and edge 28 is bent at an oblique angle, as shown in the figure, so that fixture 20 resists rotation in both clockwise and counterclockwise directions about its axis 30.

[0089] Figures 2A and 2B are schematic, sectional representations of a self-expanding intramedullary fixture 36, similar to fixture 20, illustrating the principle of radial self-expansion of such fixtures, in accordance with an example useful for understanding the present invention. For simplicity of illustration, fixture 36 comprises only a single sheet 38 of self-expanding material, preferably resilient material. It will be understood that intramedullary fixtures based on the principles of the present invention, as exemplified by fixtures 20 and 36, may comprise one, two, or more sheets of self-expanding material, rolled together as shown in Figures 1, 2A and 2B.

[0090] Figure 2A shows fixture 36 in a first, closed configuration, in which the fixture is compressed radially inward to facilitate its insertion into the intramedullary cavity of a fractured bone, as described below. For fixation of phalanx bones of the fingers, for example, fixture 36 preferably has an outer diameter of only about 2 mm in this closed configuration. Figure 2B shows fixture 36 in a second, open configuration, which the fixture assumes after location within the cavity to fixate the bone. Preferably, the diameter of fixture 36, in the open configuration of Figure 2B, is at least 50% greater than the diameter in the closed configuration of Figure 2A. More preferably, the diameter in the open configuration is approximately twice the diameter in the closed configuration. In the case of phalanx bone fixation, for example, the diameter in the open configuration is preferably approximately 4 mm. The large diameter difference between closed and open configurations is advantageous in that it facilitates insertion of fixture 36 into the bone in the closed configuration through a hole of minimal size made at or near the end of the broken bone.

[0091] As described above with reference to fixture 20, sheet 38 preferably comprises a superelastic material, preferably Nitinol, having a thickness of about 0.2 mm. The superelasticity of sheet 38 causes fixture 36 to expand until outer edges 39 of the sheet engage the inner bone surface surrounding the intramedullary cavity, to exert strong outward radial force on the bone.

[0092] Sheet 38 may comprise shape memory material, such as Nitinol, which is produced, as is known in the art, so as to have the open form shown in Figure 2B and to be normally in the austenitic state at body temperature. In the closed configuration shown in Figure 2A,

however, the force exerted in rolling up sheet 38 preferably causes the material to assume a state of stress-induced martensite. In this state, the material is relatively flexible and elastic, making it easier to insert fixture 36 into the bone. Once the fixture has expanded inside the bone to the open configuration shown in Figure 2B, however, the stress on sheet 38 is reduced, and the material reverts to its normal, substantially rigid austenitic state. The rigidity of the material in this state facilitates firm fixation of the bone.

[0093] Additionally or alternatively, the shape memory material may have a critical temperature in the range between room temperature and body temperature, preferably around 30°C. As described above, the shape memory material is formed so that in its austenitic state (i.e. above the critical temperature), it has substantially the open, expanded form shown in Figure 2B. Below the critical temperature, i.e. before insertion of fixture 36 into the bone, the shape memory material is in a martensitic state, in which it is relatively flexible and elastic and is compressed into the closed configuration shown in Figure 2A. When the fixture is inserted into the bone, it is warmed (e.g. by body heat) to above the critical temperature, whereupon it opens and assumes its substantially rigid, austenitic state. A heating element may be brought into contact with the fixture once it is inside the bone, for example, as illustrated in Figure 3B and described below, to hasten its expansion and state change.

[0094] Figures 3A-3C are schematic, sectional illustrations showing the insertion of a fixture 20 into intramedullary cavity 40 of a fractured bone 42, in accordance with a preferred embodiment of the present invention. Although described with reference to a phalanx bone, it will be appreciated that devices in accordance with the principles of the present invention may be applied in the fixation of other long bones (e.g. the humerus), with appropriate adaptations for the differences in size and mechanical strength required of the bones, as will be apparent to one of ordinary skill in the art.

[0095] As shown in Figure 3A, a stylette 46 is inserted into a lumen 47 within a cannula 48. For fixation of phalanx bones, cannula 48 preferably comprises a syringe needle. Stylette 46 and cannula 48 are then introduced percutaneously into intramedullary cavity 40 through an opening 45 at the end of bone 42, and past a fracture site 44 in the bone.

[0096] Alternatively, a small incision may be made through the skin and soft tissues, to visualize the bone, and a hole may be drilled in the bone for insertion of the cannula therethrough. Drilling such a hole is the preferable method for inserting fixtures, in accordance with some preferred embodiments of the present invention, particularly for larger bones, such as the humerus. Drilling the hole before inserting the fixture also makes it easier to remove the fixture, if desired, after the bone has healed.

[0097] As shown in Fig. 3B, once cannula 48 is properly in place, stylette 46 is withdrawn, and fixture 20, in its

compressed, closed configuration, is passed into lumen 47 of the cannula. Preferably, a plunger 43 is used to push the fixture into the needle and hold it in place. Cannula 48 is then fully withdrawn, leaving fixture 20 in cavity 40, with the fixture extending across fracture site 44.

[0098] Fixture 20 then expands or is expanded to substantially fill cavity 40, as shown in Figure 3C. As disclosed below, the fixture is expanded using external force or energy.

[0099] The self-expansion of the fixture forces curved edges 26 and 28 of sheets 22 and 24 (or 39 of fixture 36) radially outward against inner surface 49 of bone 42 across both sides of fracture site 44. This force anchors the fixture in place and prevents relative motion of the sections of the fractured bone. In some examples useful for understanding the present invention, wherein sheets 22 and 24 comprise shape memory material as described above, plunger 43 may optionally comprise a heating element for heating fixture 20 to above the critical temperature.

[0100] After fixture 20 is positioned and anchored firmly in place, plunger 43 is withdrawn through opening 45, and the skin wound made by or for cannula 48 is allowed to close. Within a short time after completion of the procedure illustrated in the figures, the subject is able to mobilize fractured bone 42. The mechanical strength of fixture 20 also reinforces the bone against axial and lateral forces that may be exerted on the bone. Moreover, the risk of post-operative infection is minimized since no surgical devices or appliances are left protruding through the skin, in contrast to the expandable intramedullar fixtures known in the art. If desired, the device can be covered with a sheath so as to prevent bone ingrowth and facilitate subsequent device removal.

[0101] Figure 4A is a schematic, isometric view of another self-expanding intramedullar fixture 50, in accordance with another example useful for understanding the present invention. Fixture 50 comprises a plurality of longitudinal ribs 52, connected by a plurality of circumferential struts 54. Ribs 52 and struts 54 preferably comprise resilient material, preferably superelastic material, or alternatively, shape memory material as described above. Figure 4A shows fixture 50 in a substantially open configuration, which the fixture assumes when it is located inside the bone and allowed to expand.

[0102] Figure 4B is a schematic, sectional illustration, showing fixture 50 in a closed or constricted configuration for insertion of the fixture into the bone. To compress the fixture into this closed configuration, a long, cylindrical holding pin 56 (seen in sectional view in Figure 4B) is inserted gradually along central axis 30 of the fixture. As pin 56 is inserted, each circumferential strut 54 is, in turn, bent inward across axis 30. Pin 56 passes through and "captures" or locks the struts in place as they are bent, thus preventing the struts from snapping back to their outward circumferential position. As struts 54 are bent inward and captured by pin 56, ribs 52 are drawn inward as well, as shown in Figure 4B. By passing pin 56 along

the entire length of axis 30 through fixture 50, the fixture is brought into the closed configuration, wherein its outer diameter is substantially reduced. Preferably the diameter or dimension of the fixture in the closed configuration of Figure 4B is reduced to no more than half the diameter in the open configuration shown in Figure 4A.

[0103] Once fixture 50 has been inserted into the intramedullar cavity of a bone (for example, cavity 40 of bone 42, as illustrated in Figures 3A-3C), pin 56 is removed. Upon removal of the pin, struts 54 spring back to their original, circumferential positions, and the fixture resumes the open configuration shown in Figure 4A.

[0104] As described above, fixture 50 may, if desired, be made of shape memory material, which in its normal, austenitic state maintains the open configuration with substantial rigidity. As struts 54 are bent, they assume a state of stress-induced martensite, returning to the austenitic state when the stress is removed as pin 56 is removed. As discussed above, if desired, this device can be covered with a sheath or sleeve (such as an expandable flexible polymer) to prevent bone ingrowth.

[0105] As a further example useful for understanding the present invention to those described above, another self expandable bone fixator is shown in Figure 5. The preferred material for this device is Nitinol, although the device can also be made from a polymer, stress-induced martensite (SIM), smooth tin, or other suitable materials.

[0106] In accordance with an example useful for understanding the present invention, Figure 5A is a schematic, end view of this self-expanding intramedullar fixture 60 in an open configuration. Fixture 60 is preferably formed of resilient material, more preferably superelastic material, as described above. The fixture comprises a plurality of leaves 62, 66, 68, 70, 72, 74, 76 and 78, extending radially outward in a spiral pattern about axis 30 of the fixture, the leaves extending from a central, generally tubular portion 63. As shown in the figure, each of the leaves extends outward at a different angle about axis 30 (as measured off of a single reference line, not shown, extending from the axis to a point located at 0 (zero) degrees on the circumference). In the expanded configuration of Figure 5A, the leaves engage the inner surface of the intramedullar cavity of a fractured bone (for example, surface 49 of cavity 40, as shown in Figures 3A-3C), in order to hold fixture 60 in place and fixate the bone. Each of the leaves has a base 67, which forms a part of tubular portion 63 of the fixture, and an inward-curved end portion 64.

[0107] Figure 5B is a schematic illustration showing a flat sheet of resilient material 65, which is cut in preparation for fabrication of fixture 60, in accordance with a preferred embodiment of the present invention. Leaves 62, 66, 68, 70, 72, 74, 76 and 78 are cut out of sheet 65 in a staircase pattern, i.e. each leaf presents a step-like extension, as shown in the figure. The leaves are then rolled up, one after the other. The leaves are rolled about axis 30, in the direction indicated by arrow 79, so that in the closed configuration shown in Figure 5C, the leaves

will expand to the shape shown in Figure 5A.

[0108] Figure 5C is a schematic, sectional illustration showing fixture 60 in the closed configuration, in preparation for insertion of the fixture into the intramedullary cavity. Holding pin 56, as described above with reference to Figure 4B, is inserted along axis 30 of fixture 60. Curved end portions 64 of leaves 62, 66, 68, 70, 72, 74, 76 and 78 are bent inward and hooked around pin 56. Fixture 60 remains in this closed configuration as long as pin 56 is in place. In the closed configuration, the device maintains a smaller external diameter than the open configuration, to facilitate insertion of the device into the bone. After insertion of the fixture in the intramedullary cavity, pin 56 is withdrawn, and the resilience of the leaves causes them to spring outward, so that fixture 60 resumes the open, larger diameter, configuration shown in Figure 5A. In this larger diameter, bone fixation and support is provided as previously described above.

[0109] The device, as with the other devices in the application, can also expand by heating, taking advantage of the material's shape memory properties. As with the other embodiments of the invention disclosed herein, it can be used in treatment of examples and both intramedullary and intravertebral support.

[0110] Figure 6 is a schematic illustration of another expandable intramedullary fixture 80, comprising a balloon 82, shown here in a deflated state, in accordance with an alternative preferred embodiment of the present invention. Balloon 82 can be formed of a flexible, biocompatible plastic, for example, a sleeve of Dacron fabric, as is known in the art, sealed shut at a distal end thereof. Fixture 80 includes strong, resilient longitudinal wires 84, made of biocompatible material, stainless steel, for strengthening balloon 82. Wires 84 may preferably be woven into the Dacron fabric of balloon 82, for example. Balloon 82 is connected via an inlet port 86 to an inflation tube 88.

[0111] Balloon 82 can also be constructed from metal having one extremity sealed shut, the other extremity being provided with a valve. In a metallic embodiment, balloon 82 can likewise have longitudinal wires or bars, as discussed above. In such an embodiment, the balloon can have a thin metal wall between the longitudinal wires or bars, this thin metal preferably being bent inwardly so as to reduce the balloon profile and diameter during insertion.

[0112] Figures 7A-TD are schematic, sectional illustrations showing the use of balloon fixture 80 in fixating fractured bone 42. As described above with respect to Figures 3A - 3C, in the preferred embodiments, a hole 45 is first made in the end of fractured bone 42 to provide access to the bone's medulla. As shown in Figure 7A, fixture 80 is then inserted through hole 45 into intramedullary cavity 40 using cannula 48. Although a thin hollowed out space can be created within the medulla prior to insertion of the fixture, in the preferred embodiment, insertion of the fixture 80 using cannula 48 itself creates the intermedullary space.

[0113] Preferably, inflation tube 88 is used in place of plunger 43 (shown in Figure 3B) to push fixture 80 through the cannula 48 and position the fixture 80 within cavity 40. It is preferred that the fixture be provided with a medial longitudinal canal so as to allow insertion of the inflatable rod over a guide wire. Longitudinal wires 84 help to hold balloon 82 in a narrow, elongated profile, so as to ease the insertion of the balloon into cavity 40. After cannula 48 is withdrawn from the bone, fixture 80 is left extending through a substantial portion of cavity 40, across both sides of fracture site 44, as shown in Figure 7B.

[0114] Inflation with the non-compressible fluid is preferably accomplished with an inflator having a pressure gauge. The pressure gauge is monitored during the inflation of the fixture. When the pressure begins to rise in slope, it indicates that good alignment has been achieved of the rod within the bone's inner surface. Later, to remove the device, a hub for fixture retrieval is inserted over the proximal part of the fixture where the valve is positioned. This hub can be used to open the valve, allowing fluid to be removed so that reduction of fixture diameter can be achieved to facilitate removal.

[0115] As illustrated in Figure 7C, after fixture 80 is inserted in cavity 40, balloon 82 is inflated via tube 88. Preferably, the balloon is first inflated with water (e.g. saline), whereupon the fixture expands to fill substantially the entire width of cavity 40. At this stage, an X-ray image of bone 42 can be produced. In the image, wires 84 and the bone are both visible, so that proper positioning of the fixture 80 can be verified.

[0116] Balloon 82 is then emptied of the saline and filled with a biocompatible, solidifying fluid which fills the balloon 82 so as to fixate the bone. Preferably, the solidifying fluid comprises a monomer material that polymerizes within the balloon, or alternatively, a two component cement, such as an epoxy. The fluid's solidification is preferably catalyzed by the increased temperature and/or humidity within the bone medulla.

[0117] As shown in Figure 7D, after balloon 82 has been filled and the fluid has at least partly solidified, inlet port 86 is sealed shut, and tube 88 is withdrawn. Within a short time, the solidified fluid fully hardens, anchoring fixture 80 in place and fixating bone 42. Wires 84 provide additional mechanical strength to fixture 80, particularly improving the fixture's resistance to lateral, bending and shear forces. In a further embodiment, a sheath or cup can be located over the valve, after insertion, to prevent bone ingrowth within or into the valve.

[0118] As in the other preferred embodiments described above, the skin wound made for insertion of fixture 80 into bone 42 is closed and allowed to heal. Bone 42 may then be mobilized within a very short time after the bone fixation surgery.

[0119] If desired, after bone 42 has healed, fixture 80 may be removed through hole 45 or via an osteotomy elsewhere in bone 42. Preferably, at least a portion of the solidified fluid is drilled out or broken up, and the

fixture is then collapsed and removed. (If, in an alternate embodiment, liquid or gel is used, they are merely suctioned or pumped out, for collapse and removal of the fixture. Alternatively, in those embodiments using a valve, the valve can merely be opened so that when the rod is pulled out of the bone through a narrow canal, the rod will be caused to reduce in diameter.)

[0120] Further preferred embodiments are shown in Figures 8-11. Figures 8 and 9 illustrate embodiments in which the balloon is designed so that only a portion is inflated with fluid. As shown in the figures, the shaded sections represent the fluid filled areas of the balloon.

[0121] As an alternative to a folded construction, the expandable bone fixation device can be formed based on a lattice configuration. Representative embodiments are shown in Figure 10, which illustrates a series of perspective views of two embodiments of the configuration in both the small, constricted, diameter and the large, expanded, diameter. These embodiments can be inserted into the bone taking advantage of the self-expanding principle inherent to superelastic or shape memory alloys discussed above.

[0122] In the examples useful for understanding the present invention of Figure 10, the devices are each formed in a meshwork or lattice configuration. Figures 10(a) and 10(b) provide an illustration of a first example of this lattice configuration, while Figures 10(c) and 10(d) provide an illustration of a second example. As shown in Figures 10(a) and 10(c), a first, small profile state is illustrated for each of the devices in which the devices are compressed into small diameters d. This reduced diameter facilitates ease of insertion into the bone. Figures 10(b) and 10(d) show the respective first and second examples, each with increased diameters d' after expansion. After insertion into bone, the properties of the superelastic or shape memory material cause the device to expand outward into these expanded diameters.

[0123] Although of similar construction, these first and second examples differ in the design of their respective lattices. The first example (Figures 10A and 10B) is constructed as a lattice which is initially in a configuration that is substantially diamond shaped, and which expands outward into a series of expanded diamonds or squares. The second example is constructed as a reduced-size lattice having a series of rectangular shaped subunits, which expand outward to form a series of interconnected hexagons (six-sided polygons), like a honeycomb.

[0124] In addition to the examples shown, other meshworks or lattices may also be provided. Likewise, although the embodiments shown are preferably for use in self-expanding designs in accordance with examples useful for understanding the present invention, they can be constructed out of other materials to serve as expandable devices. Such expandable devices, as disclosed below, will expand from the reduced to the expanded diameter state upon application of suitable energy or force in accordance with embodiments of the present invention.

[0125] Figure 11 illustrates a further example useful

for understanding the present invention. The fixator is constructed as a round or square device which can be set to two heights, H1 and H2. Rigid rods or bars 85 are hinged at points 83. By applying external force 81 on the hinge 83, the height of the device can be changed, thereby providing its expansion and fixation properties at its new height, H2 (compare Figure 11B to Figure 11A).

[0126] Although examples and embodiments are described herein with reference to fixation of fractured phalanx and humerus bones, Intramedullar fixtures in accordance with the principles of the present invention may be produced and used in fixating substantially any of the body's long bones. Such fixtures may be used, for example, both in small bones of the hands and feet, such as the metacarpal and metatarsal bones, and in large bones, such as the femur.

[0127] The fixtures and minimally-invasive methods of bone fixation in accordance with the present invention, appropriately adapted for the anatomical features of the bone being fixated, have the advantages of minimizing operative trauma and damage to soft tissues. Furthermore, because no parts of the fixtures are left protruding through the skin, the risks of infection are reduced, and the patient is able to mobilize the broken bone more quickly than the prior art.

Treatment of Intervertebral Pathologies By Spinal Fusion

[0128] The principles set forth above may further be used to treat problems of the spine and vertebrae, such as in spinal fusion procedures. In accordance with examples useful for understanding the present invention, in order to achieve spine fusion, we optimally use three procedures:

1. A surgical tool is used to thoroughly extract the vertebral periosteum in the intervertebral space with the nucleus material. This enhances bone growth (osteosynthesis).
2. The intervertebral hollow and an intercommunicating spacer (shown e.g. in Figure 12-13) enable bone graft interpositioning in its lumen which, together with its porous design, enables bone tissue to grow through it and enhances bone synthesis and vertebral fusion.
3. The intervertebral spacer of the elastic type, such as a Nitinol spacer, has flexible compressive characteristics so as to enable weight bearing on the interpositioned bone and to enable bone synthesis. One material which can be used is a nitinol, sponge type material (i.e. a porous nitinol).

[0129] As the first step in the procedure, a syringe is inserted into the damaged disc area, with or without a stylet. Preferably, a surgical tool is then used to "nibble" at or erode soft tissue only, including the vertebral periosteum; without damaging the bone itself.

[0130] Once the tissue extraction has been completed, it is possible to insert the expandable intervertebral spacer or another expandable spacer percutaneously through the hollow syringe, as with the embodiments of the intramedullary fixation device disclosed above. The function of this spacer is to stabilize the vertebrae and to enhance bone growth up to bone fusion between the two vertebrae adjacent to the intervertebral spacer.

[0131] As shown in Figures 12 and 13, examples of the intervertebral bone spacer 125 or 130 are illustrated (although the device can be used for intramedullary fixation as well). The intervertebral spacer 125 or 130 is initially inserted through the syringe in the compressed, reduced diameter form illustrated in Figure 13B. This spacer, like the intramedullary fixation device, is initially maintained in a reduced diameter profile for insertion into the intervertebral space. This ability to percutaneously insert the spacer, due to the reduced diameter profile of the spacer, allows major surgery to be avoided, as disclosed above, and reduces the trauma and risk of infection to the patient.

[0132] Upon insertion of the intervertebral spacer 125 or 130 into the intervertebral space, the spacer uncoils to reach the expanded state shown in Figure 13C, by virtue of its expandable properties. As with the embodiments of the inventions disclosed above, the spacer 125 or 130 is preferably made of biocompatible metal or polymer and is initially inserted through the syringe in the compressed, reduced diameter form illustrated in Figure 13B. The spacer can also be made of materials such as annealed 316-L stainless steel, shape memory alloy (e.g. Nitinol), or a polymer such as polyurethane. In the event that annealed material is used, the spacer 125 or 130 will require the assistance of an expander to expand its diameter after insertion. This expander can be a balloon in accordance with an embodiment of the present invention inserted through the syringe which is inflated to dilate the spacer to the diameter of the intervertebral space.

[0133] As can be seen with reference to Figures 12 or 13C, the spacer 125 or 130 is provided with a series of pores or gaps 120 in its surface. These pores 120 (which are circular, rectangular, or any other shape) enhance vertebral stability by allowing bone growth through the pores, and eventually direct fusion between adjacent vertebrae, while the spacer is in place. Protrusions or spikes 153 can also be provided, which penetrate the bone surface and assist with fixation and stabilization of the spacer.

[0134] As further shown in Figures 13A and 13C, spacer 130 is provided with a locking mechanism such as one or more locking fingers 115 or teeth 119. This locking mechanism further maintains the expanded diameter of the intervertebral spacer 130 and retards or prevents compression of the spacer 130 back to its reduced diameter state. Figure 13A illustrates the use of one or more locking fingers 115 in spacer 130. When spacer 130 expands, leading edge 122 of the spacer travels past and over locking fingers 115 or teeth 119. Locking fingers 115

or teeth 119 resist retrograde movement of the leading edge 122 or contraction of the spacer 130 by trapping the leading edge 122 within the "V" shaped gap of the locking finger 115, or the groove of one of the teeth 119.

As a result, in response to the application of force to spacer 130 while it rests between the vertebrae, the spacer exhibits flexible compressive characteristics yet resists undue compression, due to the counteraction provided by the locking mechanism.

Accordingly, the combination of the thorough cleaning of the bone surface, the special spacer porous design with its flexible compressive characteristics, and the implanted bone graft, enables and enhances bone fusion in the intervertebral space and stabilization of vertebrae up to the point of bone fusion.

Intervertebral Disc Prosthesis

Reference is now made to Figures 14A and 14B, which are schematic illustrations showing an exemplary balloon prosthesis 140, for insertion in the intervertebral disc space of a patient. Figure 14A is a top view of the prosthesis, whereas Figure 14B is a sectional view, in which the balloon is shown in an inflated state, as described below.

Balloon prosthesis 140 comprises two circular pieces of biocompatible fabric 142, preferably having a diameter approximately equal to the diameter of an intervertebral disc. Fabric 142 is preferably woven out of strong, inert, synthetic fibers, such as Dacron, Gore-Tax or other fiber materials known in the art. Alternatively or additionally, the fabric may comprise bioabsorbable material, known in the art, either by itself or, preferably, interwoven with the inert fibers. The fabric preferably has a rough weave, so that after implantation of prosthesis 140, as described below, bone ingrowth into the prosthesis is enhanced.

Further alternatively, the two pieces of fabric 142 may be replaced by any suitable biocompatible material, as long as it is flexible, elastic and strong enough to be inserted into the disc space and inflated to a sufficient pressure, as described below,

It is preferred that ground bone substance (taken, for example, from the patient's pelvic bone) be placed on the outer surface of fabric 142, before and/or after implanting prosthesis 140. Moreover, a substantial quantity of the bone substance may preferably be contained in the hollow at center 146 of the balloon. The ground substance further enhances the desired bone growth and fixation to bone.

It is also preferred that the balloon further be provided with protrusions 153 in its upper and lower surfaces so as to stick and/or penetrate up and down into the bone surface. These protrusions prevent balloon movement and achieve better stabilization of the balloon.

Although preferred embodiments are described herein with reference to the generally toroidal balloon shown in Figures 14A and 14B, it will be appreciated that

the principles may be applied to produce and implant balloon prosthesis of different sizes and/or shapes, such as ellipsoidal and crescent-shaped balloons, or two parallel, cylindrical, rods.

[0142] Fabric pieces 142 are sealed to one another around their outer edge 144 and at their circular center 146. As one example, heat sealing can be used, a technique which is known in the art. One or more strong, resilient wires 152, preferably stainless steel wires, are interwoven with fabric 142 to reinforce the structure of balloon 140. Wires 152 are shown in Figures 14A and 14B at outer edge 144 of the balloon, where the presence of the wires is helpful in preventing rupture of the balloon along the seam between pieces 142. The wires are also useful in stiffening the balloon, to make it easier to manipulate and position within the disc space, as described below. Alternatively or additionally, such wires may be interwoven at other locations in fabric pieces 142. They can also be useful in positively locating the wire when used in conjunction with X-ray imaging.

[0143] A fluid port 148 is left open at a point along edge 144. An inflation tube 158 is fitted and sealed to port 148. When a pressurized fluid is injected through tube 158 into port 148, the fluid fills and inflates space 150 within balloon 140 to a predetermined fluid pressure.

[0144] Figure 15 is a schematic, isometric view illustrating the implantation of prosthesis 140 into a disc space 162 intermediate two vertebrae 164 and 166, in accordance with a preferred embodiment of the present invention. Prosthesis 140 is implanted in disc space 162 to replace an injured natural disc, e.g., a disc that has been herniated. In preparation for implantation of the prosthesis, a cannula 160 is inserted percutaneously into disc space 162, in a lateral approach. Substantially all of the natural disc matter is removed from the disc space prior to implantation of the prosthesis.

[0145] In order to insert prosthesis 140 into cannula 160, the prosthesis is rolled into a narrow, elongate, generally cylindrical form, as shown in Figure 15. The prosthesis is fed in this shape through the cannula and into now eroded out disc space 162. Preferably, inflation tube 158 is stiff enough so that it can serve to push the prosthesis through the cannula. Otherwise, other surgical probes known in the art may be used for this purpose.

[0146] It will be appreciated that the unique reduced diameter structure and flexibility of prosthesis 140, in accordance with the principles of the present invention, make it possible to implant the prosthesis through narrow cannula 40. Disc prostheses known in the art cannot be compacted in this manner nor can they be subsequently opened and inflated within disc space 162, as described below. Thus, prosthesis 140 can be implanted percutaneously, without the need for substantial skin incisions, laminectomy or dissection of large masses of muscle.

[0147] Figure 16 is a schematic, sectional view showing vertebrae 164 and 166, seen along a coronal plane therethrough, with prosthesis 140 positioned in disc space 162 between the vertebrae. Once prosthesis 140

has been fed all the way through cannula 40 and into the disc space, the prosthesis unrolls in the open space, assuming a generally flat shape (as shown in the figure), until it is inflated. The resilience of wires 152 aids the balloon fabric in unrolling. It also stiffens the fabric to make it easier to center the prosthesis in the disc space, preferably by pushing and pulling it using tube 158 through cannula 160.

[0148] Correct placement of prosthesis 140 in disc space 162 is preferably verified by visualization of the vertebrae, disc space and prosthesis, most preferably using an open magnetic resonance imaging (MRI) system. Alternatively, X-ray imaging may be used to observe the position of wires 152 relative to vertebrae 164 and 166. Further alternatively or additionally, a narrow endoscope, as is known in the art, may be inserted into or adjacent to disk space 162 to visually observe the prosthesis.

[0149] After insertion of prosthesis 140 as shown in Figure 16, the prosthesis is inflated with saline, so that it assumes the form shown in Figure 14B. Inflating the prosthesis allows it to be visualized in substantially the shape and position that it will have when filled with solidifying fluid, as described below. If the prosthesis is seen to be incorrectly positioned, it can easily be deflated, repositioned and then reinflated. After correct positioning is verified, the saline is removed and the prosthesis deflates.

[0150] Once prosthesis 140 is suitably positioned in disc space 162, a biocompatible solidifying fluid is injected through tube 158 and port 148, to inflate the prosthesis. Preferably, the solidifying fluid comprises a bone epoxy, known in the art, such as DuPuy Orthopedic Bone Cement, produced by the DuPuy Company, England. Alternatively, the solidifying fluid may comprise a polymerizing monomer.

[0151] Prosthesis 140 is inflated to such pressure as is necessary to maintain an anatomically correct spacing between vertebrae 164 and 166. Because of the elasticity of fabric pieces 142 that form the balloon and the equalization of the pressure of the fluid throughout space 150 (as seen in Figure 14), the balloon will tend naturally to maintain a generally uniform pressure on the surfaces of vertebrae 164 and 166 that adjoin disc space 162 and to hold the vertebrae in an anatomically correct mutual orientation. Preferably, vertebrae 164 and 166, along with prosthesis 140 and surrounding structures, are imaged, most preferably using MRI, as described above, to verify that the spacing and orientation of the vertebrae are correct.

[0152] When the fluid has solidified sufficiently, port 148 is sealed and tube 158 is removed, preferably by twisting and pulling tube 158 back through cannula 160.

[0153] Figures 17A and 17B are coronal and axial sectional views, respectively, showing prosthesis 140 inserted and inflated within disc space 162. The prosthesis has been inflated with solidifying fluid 170, and tube 158 has been detached and removed, as described above. Vertebrae 164 and 166 remain substantially intact, including

lamina 172, thereof.

[0154] Following the implantation of prosthesis 140, as shown in Figures 17A and 17B, vertebrae 164 and 166 will grow into disc space 162, around and through the prosthesis. Preferably, as described above, ground bone is placed on the outer surfaces of prosthesis 140, and particularly in the hollow at center 146 thereof, in order to aid this bone growth. Ultimately, the growth of vertebrae 164 and 166 will cause them to fuse together, so that the bones are permanently stabilized and protected from any further injury.

[0155] Although in the exemplary embodiments described above with reference to Figures 14-17, a single prosthesis, comparable in size to the natural intervertebral disc, is implanted in disc space 162, in other exemplary embodiments, two or more smaller prostheses may be implanted side-by-side in the disc space.

[0156] Furthermore, although in the above-described exemplary embodiment, prosthesis 140 is implanted percutaneously in a lateral approach, it will be appreciated that inflatable disc prostheses may also be implanted using other surgical techniques known in the art, such as open and laparoscopic surgical procedures with an anterior or posterior approach.

[0157] The exemplary embodiments of Figures 18A-18C present flat annular top and bottom walls, like a washer, in contrast to the donut (toroidal) shape shown in Figures 14-17. Further preferred embodiments are also described below in the following section regarding metal balloons for intramedullary fixation and disc prostheses.

Metal Balloons for Intramedullary Fixation and Disc Prosthesis

[0158] As described above, in accordance with the present inventions, a small opening is made from outside a bone to accommodate insertion of a device percutaneously into the bone (whether it be long or small bone); or, to replace a disc, a hole is made in the intervertebral space. In some of the preferred embodiments of the invention, the device includes a metallic balloon.

[0159] In the preferred embodiments, the balloon is made from thin metal such as Titanium, Tantalum, Stainless Steel (e.g. S.S. 316L), Platinum, another medical grade metal, or so forth. The balloon is preferably constructed with a balloon wall thickness between 10 and 300 microns, although wall thicknesses which are greater or less than these dimensions are possible, as well.

[0160] The balloon can be constructed with several metal strings or rods to provide the balloon with greater strength against axial, bending and rotational forces, and to provide the balloon with greater rigidity that eases its manipulation and insertion into the patient. The rods can be connected to the exterior or interior surface of the balloon (e.g. by soldering, milling or as a part of the balloon). For example, to produce the metal balloon and the rods they could all be annealed or could all be cold

worked. Alternatively, the rods could be cold worked, while the balloon itself is annealed to allow easier expansion after insertion within the bone. This can be done by producing a one piece cold worked rod and annealing afterwards only the thin wall part of the metal balloon. The balloon extremities can be manufactured by soldering, spot welding, laser welding or any other suitable way of connecting the metal cone to each extremity of the device.

[0161] The outer surface of the balloon may be abrasive or roughened with protruding edges engaging the bone surface to anchor the fixture firmly in place and prevent sliding or rotation of the parts of the broken bone in the intramedullary embodiments, or, likewise provide non-movement in the intervertebral embodiments. This system has the advantage of not requiring or using interlocking screws in intramedullary nailing.

[0162] Additionally, or alternatively, the balloon can comprise a biocompatible polymer. Additionally or alternatively, the balloon can comprise an outer thin surface of metal as described above and an inner surface of biocompatible plastic, polymer or fabric.

[0163] Once the balloon has been inserted into its proper place within the bone or adjacent to the vertebrae, it is then inflated with a biocompatible material. In the preferred embodiments, a liquid is used as the inflation fluid in intramedullary fixation, and a biocompatible solidifying fluid is used as a disc prosthesis. As liquids for intramedullary fixation, water, gel or air are preferred. As a further alternative, however, a solidifying fluid can be used, if desired.

[0164] In alternative embodiments of the invention, the inflation fluid (either for the intramedullary nail or the disc prosthesis) is a filler material which is itself capable of expansion. This filler material is preferably capable of changing its volume or stiffness in response to an external stimulus. For example, the external stimulus can be a magnetic field, an electric field, radiation and/or temperature. Rheological materials, polyelectrolyte gels or other suitable expandable materials which change their volume or stiffness in response to external stimuli can be used as the filler material.

[0165] This inflation fluid is placed in communication with the lumen of the balloon, while also being under pressure from an external source, causing the balloon to expand radially outward to fixate the bone. The balloon is then sealed, e.g. by using a valve, and the external fluid source is disconnected. In the valve embodiments, it is preferred that a protective cup be provided over the valve to shield and protect the valve from bone ingrowth.

[0166] In the embodiments using a solidifying fluid, the disc prosthesis becomes extremely strong and can replace the disc. This balloon can also be provided with one or more tunnels or holes between surfaces that allow the vertebral bone surfaces to contact each other between two adjacent vertebrae, thereby enabling those two vertebrae to undergo fusion. In addition, the outside surface of the metal balloon is stronger than the verte-

brae, which keeps the vertebrae from eroding. The outside surface of the metal balloon can also be abrasive or roughened, and be provided with protruding edges to engage the vertebrae and anchor the fixture firmly in place, preventing sliding or rotation.

[0167] Additionally or alternatively, the balloon can comprises a biocompatible plastic which is of sufficient strength that it is stronger than the vertebrae. Additionally or alternatively, the balloon comprises an outside surface of metal as described above and an inner surface of biocompatible plastic or fabric.

[0168] In the case of the intramedullary device, once the bone has healed, the balloon can be deflated by opening the valve and removing the liquid, thereby easing the device's removal. In the case of the intervertebral disc prosthesis, the prosthesis may be left in place permanently.

[0169] Figures 20-23 illustrate some preferred embodiments of the present invention. These embodiments are useful with respect to the intramedullary nail, and the balloon embodiments of the nail, in particular, although features of these embodiments can also be used in conjunction with self-expanding or expandable devices and/or in conjunction with the other intervertebral devices and prostheses disclosed herein. Thus, the valve, fixation elements, etc. can also be used with the other inventions disclosed in the present disclosure. Figure 20 illustrates an additional preferred embodiment of the intramedullary nail or fixture of the present inventions. As shown in the figures, it is preferred that the nail be constructed having longitudinal, outwardly extending, bars 300. Figure 20B is a cross sectional view illustrating the protuberance of longitudinal bars 300 above the surface of intramedullary nail 310. These longitudinal bars 300 may be placed upon a portion of the length of intramedullary nail 310, although it is preferred that they extend along all, or substantially all, of the length of the intramedullary nailing device. In the preferred embodiment, as shown in the figure, four longitudinal bars are provided, located at 90 degree intervals around the nail's circumference. Alternatively, other numbers of longitudinal bars can be provided as well.

[0170] Longitudinal bars 300 act as fixational elements, improving the function of the device and facilitating bone healing. When the intramedullary nail is inflated, the longitudinal bars or fixational elements 300 are pressed against the inner surface of the bone cortex, preventing rotational movement between the broken parts of the bone and preventing bending. The addition of these fixational elements presents an advantage over standard intramedullary nails as no interlocking is needed due to the fact that the longitudinal rods prevent rotation. This further stabilizes the bone, and facilitates the healing process. These longitudinal bars or fixational elements 300 can be provided to various embodiments of the present invention, whether the self expandable, balloon expandable, or balloon embodiments, disclosed herein.

[0171] Figure 21 illustrates additional aspects of a pre-

ferred embodiment of the intramedullary fixture disclosed herein. As shown in the figure, in preferred embodiments of the invention, a metal balloon or fixture 320 is utilized having a pipe or body 321 and a distal end cover 323. Metal balloon or fixture 320 is further provided with a valve 318 located at proximal tip 330 of the fixture for controlling the passage of fluid into and out of fixture 320. Valve 318 includes ventilation pin 325, O-ring 326, and spring 327 housed within a head cover 322, and terminating in a head cap 328. Head cover 322 and head cap 328 shield valve 318, preventing bone growth into the valve.

[0172] In a preferred embodiment, a high pressure fluid (e.g. saline) is first inserted or pumped into the intramedullary fixture through valve 318. Pumping of the saline into the balloon through the valve causes fixture 320 to expand in diameter, as shown in comparison of Figure 21B to Figure 21C. The valve prevents fluid from escaping the intramedullary fixture, maintaining the fixture in the expanded state for the length of time needed. If desired, the fixture can be subsequently deflated using valve 318 to release fluid or saline from the fixture.

[0173] A further embodiment of the invention is illustrated in Figure 21D. The invention is illustrated as located within a bone 313. The fixture is provided with a tubular element 311 for location in the vicinity of the bone fracture. Element 311 is of a fixed diameter less than the diameter of inflated fixture segments 315. The diameter of element 311 is fixed such that upon radial expansion of the fixture, element 311 prevents or restrains expansion of the fixture so that it cannot contact the inner bone surface. Thus, although segments 315 expand to a diameter which contacts the inner surface of the bone, element 311 prevents the fixture surrounded by the element from achieving the degree of expansion achieved by the remainder of the fixture. The device, for example, can be provided with a ring for restraining expansion of in that area. This embodiment is particularly useful to prevent "butterfly fractures", or complications in fractures with multiple bone fragments.

[0174] An embodiment of the intramedullary nail of the present invention is disclosed in Figure 22A. Figure 22A consists of two cross sectional views of a fixture embodiment, both before and after expansion, these views being superimposed on each other (for appreciation of relative constricted and expanded diameters). In this embodiment of the invention, the constricted intramedullary nail includes a curved or undulated surface, preferably having longitudinal bars 300 located thereon. It is preferred that intramedullary fixture, before expansion, have its surface be curved or folded inward to form a series of connected bulbous sections 336. In the preferred embodiment, the bulbous sections form a clover like configuration in the compressed state, as shown in the four leaf clover configuration illustrated in Figure 22A.

[0175] As shown in Figure 22A, in the compressed configuration or state 332, intramedullary nail 330 maintains a compressed diameter D_1 . Compressed diameter

D_1 is a small diameter such that the intramedullar nail is suitable for insertion into the bone through a small hole in the bone or through a syringe, as discussed above. In contrast, in the expanded configuration or state 334, the intramedullar nail 330 is maintained within the bone at an expanded diameter D_2 . Expanded diameter D_2 is a larger diameter, measured from the outside surface of longitudinal bar 301 to the outside surface of opposing longitudinal bar 302, this diameter being sufficient such that the longitudinal bars are pressed up against the inner wall of the desired bone. The figure, although not to scale, shows both the compressed and expanded states of the fixture superimposed on each other, illustrating the substantial increase of diameter achieved by inflation of the fixture from the compressed to the expanded state.

[0176] Figure 22B is a further embodiment of the invention, illustrated in the same manner as in Figure 22A. In this embodiment, one or more hairpin loops or arcs 337 are provided between longitudinal bars 300. In the embodiment shown, four longitudinal bars 300 are provided, each at 90 degrees to each other, with one hairpin loop 337 centrally located between and connecting each adjacent pair of longitudinal bars. One or more or no hairpin loops can be provided between any or all of the pairs of adjacent longitudinal bars, if desired.

[0177] As shown in Figures 23A and 23B, in preferred embodiments, the intramedullar nail can also be provided with a medial longitudinal canal, bore or tunnel 344. This canal 344 facilitates the insertion of the nail into the bone, allowing the insertion procedure to be performed using a guide wire. The medial canal 344 is threaded over the guide wire to allow the fixture to be easily guided into the appropriate position during insertion into the bone, and to allow the guide wire to be pulled out once positioning has been completed.

[0178] Particularly in the embodiments having a valve, a retrieval mechanism can be provided which is mounted on the tip of the implanted nail to assist in withdrawal of the nail from the bone. Upon mounting the retrieval device on the tip of the valve, the valve can be opened, releasing the high pressure within the nail and thereby allowing the diameter to decrease in preparation for removal.

[0179] In summary, the above descriptions of the present invention describe minimally invasive insertion of intramedullary. It must be understood that, although preferred embodiments are described, the embodiments of the present inventions are directed to expandable fixation and prosthesis devices which expand by an expander inserted through its lumen to an expansion level that enables percutaneous insertion of the bone fixator.

[0180] Having described the inventions with regard to specific embodiments, is to be understood that the present application covers all variations and modifications of the inventions as fall within the scope of the claims.

Claims

1. A medical device for treatment of broken bones having an intramedullary cavity, the bone being provided with a bore formed through the exterior surface of the bone and extending into the intramedullary cavity, comprising:

a bone fixture (320) for insertion through the bore of the bone and into the intramedullary cavity, said bone fixture comprising an inflatable, diameter-expandable tube having an exterior circumferential surface, said tube (321) having a reduced first diameter for insertion through the bore and into the intramedullary cavity and a second expanded diameter, wherein said bone fixture (320) will radially increase in diameter from said reduced first diameter to said expanded second diameter by inflation when fluid is supplied to the interior of said device, and when said bone fixture (320) radially increases in diameter from said reduced first diameter to said second expanded diameter, at least a portion of said exterior circumferential surface coming into contact with a portion of the side wall of said intramedullary cavity upon said bone fixture (320) increasing to said second expanded diameter, **characterised in that** said tube is a non-memory metallic tube.

2. A medical device as claimed in claim 1, wherein said device is basically cylindrical when expanded to said second expanded diameter.
3. A medical device as claimed in claim 1 further comprising at least one rib longitudinally extending along the exterior circumferential surface of said bone fixture.
4. A medical device as claimed in claim 1, wherein at least two ribs longitudinally extend along the exterior circumferential surface of said bone fixture.
5. A medical device as claimed in claim 4, wherein said ribs define wall web portions therebetween and said wall web portions are folded upon themselves prior to expansion of said bone fixture.
6. A medical device as claimed in claim 1, further comprising four ribs longitudinally extending along the exterior circumferential surface of said bone fixture.
7. A medical device as claimed in claim 5, wherein said wall web portions are initially, pre-expansion, folded into individual bulbous sections, said sections being approximately S-shaped.
8. A medical device as claimed in claim 5, wherein said

device comprises four of said longitudinal ribs and wherein said wall web portions are initially, pre-expansion, folded into individual bulbous sections, said bulbous sections being approximately S-shaped.

9. A medical device as claimed in claim 5, wherein each of said wall web portions are folded, pre-expansion, into a hairpin-like loop. 5
10. A medical device as claimed in claim 5, wherein said device comprises four of said longitudinal ribs and wherein each of said wall web portions are curved, pre-expansion, into a hairpin-like loop. 10
11. A medical device as claimed in either of claims 1 or 3 wherein said metallic tube is manufactured of a material selected from the group comprising: titanium, stainless steel and SS316. 15
12. A medical device as claimed in either of claims 1 or 3, wherein said reduced first diameter is sufficiently small such that said bone fixture can be inserted into the bore of the bone through a syringe. 20
13. A medical treatment device as claimed in either of claims 1 or 3, wherein said bone fixture is sized for treatment of a broken bone selected from the group comprising: the hand, the foot, the leg and the arm. 25
14. A medical device as claimed in either of claims 1 or 3, wherein said device further comprises a restraining means for restraining radial expansion of a portion of said device, when said device expands from said reduced first diameter to said expanded second diameter. 30
35
15. A medical device as claimed in either of claims 1 or 3, wherein said bone fixture increases in diameter by at least 40% when said fixture increases from said reduced first diameter to said expanded second diameter. 40
16. A medical device as claimed in either of claims 1 or 3, wherein said bone fixture is supplied with a valve, at least allowing for one-way fluid flow, for selective entry of the fluid into the interior of said device. 45
17. A medical device as claimed in claim 16, wherein said valve is bi-directional. 50
18. A medical device as claimed in claim 3, wherein said bone fixture is in the basic shape of a cylinder tapered on at least one end. 55
19. A medical treatment system comprising a medical device according to any preceding claim and a cannula (48) for insertion of said bone fixture (320) into a bone, said cannula comprising a lumen, said bone

fixture being of a sufficiently small size in said reduced diameter that said bone fixture (320) can be inserted into said bone by use of said cannula.

Patentansprüche

1. Medizinische Vorrichtung für die Behandlung von gebrochenen Knochen mit einem intramedullären Hohlraum, wobei der Knochen mit einem Bohrloch versehen ist, das durch die Außenfläche des Knochens gebildet wird und sich in den intramedullären Hohlraum erstreckt, das aufweist:

eine Knochenhalterung (320) für das Einsetzen durch das Bohrloch des Knochens und in den intramedullären Hohlraum, wobei die Knochenhalterung einen aufblasbaren, im Durchmesser expandierbaren Schlauch mit einer äußeren Umfangsfläche aufweist, wobei der Schlauch (321) einen verringerten ersten Durchmesser für ein Einsetzen durch das Bohrloch und in den intramedullären Hohlraum hinein und einen zweiten expandierten Durchmesser aufweist, wobei die Knochenhalterung (320) im Durchmesser vom verringerten ersten Durchmesser zum expandierten zweiten Durchmesser durch Aufblasen radial größer wird, wenn Fluid dem Inneren der Vorrichtung zugeführt wird, und wobei, wenn die Knochenhalterung (320) im Durchmesser vom verringerten ersten Durchmesser zum zweiten expandierten Durchmesser radial größer wird, mindestens ein Abschnitt der äußeren Umfangsfläche mit einem Abschnitt der Seitenwand des intramedullären Hohlraumes in Berührung kommt, wenn sich die Knochenhalterung (320) auf den zweiten expandierten Durchmesser vergrößert, **dadurch gekennzeichnet, dass** der Schlauch ein Nichtmetymetallschlauch ist.

2. Medizinische Vorrichtung nach Anspruch 1, bei dem die Vorrichtung im Grunde genommen zylindrisch ist, wenn es bis zum zweiten expandierten Durchmesser expandiert wird.
3. Medizinische Vorrichtung nach Anspruch 1, das außerdem mindestens eine Rippe aufweist, die sich in Längsrichtung entlang der äußeren Umfangsfläche der Knochenhalterung erstreckt.
4. Medizinische Vorrichtung nach Anspruch 1, bei dem sich mindestens zwei Rippen in Längsrichtung entlang der äußeren Umfangsfläche der Knochenhalterung erstrecken.
5. Medizinische Vorrichtung nach Anspruch 4, bei dem die Rippen Wandstegabschnitte dazwischen defi-

- nieren und die Wandstegabschnitte vor der Expansion der Knochenhalterung auf sich selbst gefaltet werden.
6. Medizinische Vorrichtung nach Anspruch 1, das außerdem vier Rippen aufweist, die sich in Längsrichtung entlang der äußeren Umfangsfläche der Knochenhalterung erstrecken. 5
 7. Medizinische Vorrichtung nach Anspruch 5, bei dem die Wandstegabschnitte anfangs, vor der Expansion, zu einzelnen bauchigen Abschnitten gefaltet werden, wobei die Abschnitte annähernd S-förmig sind. 10
 8. Medizinische Vorrichtung nach Anspruch 5, bei dem die Vorrichtung vier der Längsrippen aufweist, und bei dem die Wandstegabschnitte anfangs, vor der Expansion, zu einzelnen bauchigen Abschnitten gefaltet werden, wobei die Abschnitte annähernd S-förmig sind. 15 20
 9. Medizinische Vorrichtung nach Anspruch 5, bei dem ein jeder der Wandstegabschnitte vor der Expansion zu einer haarnadelartigen Struktur gefaltet wird. 25
 10. Medizinische Vorrichtung nach Anspruch 5, bei dem die Vorrichtung vier der Längsrippen aufweist, und bei dem ein jeder der Wandstegabschnitte vor der Expansion zu einer haarnadelartigen Struktur gebogen wird. 30
 11. Medizinische Vorrichtung nach entweder Anspruch 1 oder 3, bei dem der Metallschlauch aus einem Material hergestellt wird, das aus der Gruppe ausgewählt wird, die aufweist: Titan, nichtrostenden Stahl und SS316. 35
 12. Medizinische Vorrichtung nach entweder Anspruch 1 oder 3, bei dem der verringerte erste Durchmesser ausreichend klein ist, so dass die Knochenhalterung mittels einer Spritze in das Bohrloch des Knochens eingesetzt werden kann. 40
 13. Medizinische Vorrichtung nach entweder Anspruch 1 oder 3, bei dem die Knochenhalterung für eine Behandlung eines gebrochenen Knochens bemessen ist, ausgewählt aus der Gruppe, die aufweist: die Hand, den Fuß, das Bein und den Arm. 45 50
 14. Medizinische Vorrichtung nach entweder Anspruch 1 oder 3, bei dem die Vorrichtung außerdem ein Einschränkungsmittel für das Einschränken der radialen Expansion eines Abschnittes der Vorrichtung aufweist, wenn die Vorrichtung vom verringerten ersten Durchmesser zum expandierten zweiten Durchmesser expandiert. 55

15. Medizinische Vorrichtung nach entweder Anspruch 1 oder 3, bei dem die Knochenhalterung im Durchmesser um mindestens 40 % größer wird, wenn sich die Halterung vom verringerten ersten Durchmesser zum expandierten zweiten Durchmesser vergrößert.
16. Medizinische Vorrichtung nach entweder Anspruch 1 oder 3, bei dem die Knochenhalterung mit einem Ventil geliefert wird, das mindestens einen Einwegfluidstrom für einen selektiven Eintritt des Fluids in das Innere der Vorrichtung gestattet.
17. Medizinische Vorrichtung nach Anspruch 16, bei dem das Ventil ein Zweirichtungsventil ist.
18. Medizinische Vorrichtung nach Anspruch 3, bei dem die Knochenhalterung in der Grundform ein Zylinder ist, der an mindestens einem Ende kegelförmig ist.
19. Medizinisches Behandlungssystem, das aufweist: ein medizinische Vorrichtung nach einem der vorhergehenden Ansprüche; und eine Kanüle (48) für das Einsetzen der Knochenhalterung (320) in einen Knochen, wobei die Kanüle einen Hohlraum aufweist, wobei die Knochenhalterung von einer ausreichend kleinen Größe beim verringerten Durchmesser ist, damit die Knochenhalterung (320) bei Benutzung der Kanüle in den Knochen eingesetzt werden kann.

Revendications

1. Dispositif médical pour le traitement d'os cassés, comprenant une cavité intramédullaire, l'os étant muni d'un alésage formé à travers la surface externe de l'os et s'étendant dans la cavité intramédullaire, comprenant :

un dispositif de fixation de l'os (320) destiné à être inséré à travers l'alésage de l'os et dans la cavité intramédullaire, ledit dispositif de fixation de l'os comprenant un tube gonflable à diamètre dilatable, comportant une surface circonferentielle externe, ledit tube (321) ayant un premier diamètre réduit en vue de l'insertion à travers l'alésage et dans la cavité intramédullaire, et un deuxième diamètre dilaté, ledit dispositif de fixation de l'os (320) ayant un diamètre à accroissement radial, dudit premier diamètre réduit vers ledit deuxième diamètre dilaté, par gonflement lors de l'alimentation de fluide à l'intérieur dudit dispositif, ledit dispositif de fixation de l'os (320) ayant un diamètre à accroissement radial, dudit premier diamètre réduit vers ledit deuxième diamètre dilaté, au moins une partie de ladite surface circonferentielle externe entrant en contact avec une partie de la paroi latérale de ladite

- cavité intramédullaire lors de l'accroissement du diamètre dudit dispositif de fixation de l'os (320) vers ledit deuxième diamètre dilaté, **caractérisé en ce que** ledit tube est un tube métallique sans mémoire de forme.
2. Dispositif médical selon la revendication 1, dans lequel ledit dispositif est essentiellement cylindrique lors de la dilatation vers ledit deuxième diamètre dilaté.
 3. Dispositif médical selon la revendication 1, comprenant en outre au moins une nervure s'étendant longitudinalement le long de la surface circonférentielle externe dudit dispositif de fixation de l'os.
 4. Dispositif médical selon la revendication 1, dans lequel au moins deux nervures s'étendent longitudinalement le long de la surface circonférentielle externe dudit dispositif de fixation de l'os.
 5. Dispositif médical selon la revendication 4, dans lequel lesdites nervures définissent des parties de bande de paroi entre elles, lesdites parties de bande de paroi étant repliées sur elles-mêmes avant la dilatation dudit dispositif de fixation de l'os.
 6. Dispositif médical selon la revendication 1, comprenant en outre quatre nervures s'étendant longitudinalement le long de la surface circonférentielle externe dudit dispositif de fixation de l'os.
 7. Dispositif médical selon la revendication 5, dans lequel lesdites parties de bande de paroi sont pliées initialement, avant la dilatation, en des sections bulbeuses individuelles, lesdites sections ayant pratiquement une forme en S.
 8. Dispositif médical selon la revendication 5, dans lequel ledit dispositif comprend quatre desdites nervures longitudinales, lesdites parties de bande de paroi étant initialement, avant la dilatation, pliées en des sections bulbeuses individuelles, lesdites sections bulbeuses ayant pratiquement une forme en S.
 9. Dispositif médical selon la revendication 5, dans lequel chacune desdites parties de bande de paroi est pliée après la dilatation en une boucle en épingle à cheveux.
 10. Dispositif médical selon la revendication 5, dans lequel ledit dispositif comprend quatre desdites nervures longitudinales, chacune desdites parties de bande de paroi étant courbée avant la dilatation en une boucle en épingle à cheveux.
 11. Dispositif médical selon l'une des revendications 1 ou 3, dans lequel ledit tube métallique est fabriqué à partir de matériau sélectionné dans le groupe constitué de : titane, acier inoxydable et SS316.
 12. Dispositif médical selon l'une des revendications 1 ou 3, dans lequel ledit premier diamètre réduit est suffisamment réduit pour permettre l'insertion dudit dispositif de fixation de l'os dans l'alésage de l'os par l'intermédiaire d'une seringue.
 13. Dispositif de traitement médical selon l'une des revendications 1 ou 3, dans lequel ledit dispositif de fixation de l'os est dimensionné pour le traitement d'un os cassé, sélectionné dans le groupe constitué de : la main, le pied, la jambe et le bras.
 14. Dispositif médical selon l'une des revendications 1 ou 3, dans lequel ledit dispositif comprend en outre un moyen de retenue pour contenir la dilatation radiale d'une partie dudit dispositif lorsque ledit dispositif est dilaté dudit premier diamètre réduit vers ledit deuxième diamètre dilaté.
 15. Dispositif médical selon l'une des revendications 1 ou 3, dans lequel ledit dispositif de fixation de l'os a un diamètre accru d'au moins 40% lors de l'accroissement du diamètre dudit dispositif de fixation dudit premier diamètre réduit vers ledit deuxième diamètre dilaté.
 16. Dispositif médical selon l'une des revendications 1 ou 3, dans lequel ledit dispositif de fixation de l'os est équipé d'une soupape, permettant au moins un écoulement de fluide dans une direction, en vue d'une entrée sélective du fluide à l'intérieur dudit dispositif.
 17. Dispositif médical selon la revendication 16, dans lequel ladite soupape est bidirectionnelle.
 18. Dispositif médical selon la revendication 3, dans lequel ledit dispositif de fixation de l'os a la forme de base d'un cylindre effilé au niveau d'au moins une extrémité.
 19. Système de traitement médical, comprenant un dispositif médical selon l'une quelconque des revendications précédentes, et une canule (48) pour l'insertion dudit dispositif de fixation de l'os (320) dans un os, ladite canule comprenant une lumière, ledit dispositif de fixation de l'os ayant une taille suffisamment réduite en présence dudit diamètre réduit pour permettre l'insertion dudit dispositif de fixation de l'os (320) dans ledit os par l'intermédiaire de ladite canule.




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B





FIG. 3C






FIG. 4A

FIG. 4B

FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C





FIG. 7D






FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 11A





FIG. 11B

FIG. 12






FIG. 13B




FIG. 13A




FIG. 13C

FIG. 14A





FIG. 14B







FIG. 16






FIG. 17A




FIG. 17B




FIG. 18A




FIG. 18B




FIG. 18C





FIG. 19



SECTION A-A

PACKED

INFLATED




FIG. 218

FIG. 219




FIG. 21A




FIG. 210




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 4204531 A, Aginsky [0005] [0013]
- US 4854312 A, Raftopoulos [0006] [0013]
- US 4313434 A, Segal [0007]
- US 5423850 A [0008] [0016]
- US 5480400 A, Berger [0008] [0016]
- WO 9412112 A [0013]
- US 5520690 A [0018]
- US 5522816 A [0018]
- US 5529899 A [0018]
- US 4759769 A [0019]
- WO 9214423 A [0019]
- WO 9000037 A [0019]
- WO 9637170 A [0019]
- US 4904260 A [0019] [0023]
- US 5645598 A [0019]
- US 4772287 A [0023]
- US 3875595 A [0024]
- US 4349921 A [0024]
- US 3867728 A [0024]
- US 4554914 A [0024]
- US 4309777 A [0024]
- US 3426364 A [0024]
- US 4636217 A [0024]
- US 5131382 A [0028]
- WO 9611643 A [0029]
- WO 9632899 A [0030]
- EP 0493789 A [0031]

Non-patent literature cited in the description

- **VARELA ; CARR.** Closed Intramedullary Pinning of Metacarpal and Phalanx Fractures. *Orthopedics*, 1990, vol. 13 (2), 213-215 [0011]
- **LEWIS, R.C., JR. ; NORDYKE, M. ; DUNCAN, K.** *Clinical Orthopedics Related Research*, 1987, vol. 214, 85-92 [0013]
- **NORDYKE, M.D. ; LEWIS, R.C. ; JANSSEN, H.F. ; DUNCAN, K.H.** *J. of Hand Surgery*, 1988, vol. 13/11, 128-134 [0013]
- **VARELA; C.D. ; CARR, J.B.** *Orthopedics*, 1990, vol. 13/2, 213-215 [0013]
- **ROYCE C. LEWIS et al.** Expandable Intramedullary Device for the Treatment of Fractures in the Hand. *Clinical Orthopedics and Related Research, Tech. Ortho.*, 1989, vol. 1, 18-91 [0014]
- **VARELA, C.D. ; CARR, J.B.** Closed intramedullary pinning of metacarpal fractures. *Orthopedics*, 1990, vol. 13/2, 213-215 [0015]